## Window and Door Selection Chart



All products feature a pour and debridge polyurethane thermal break utilizing *Azo-Brader*™ technology with a 10-year pass-through warranty against failure of the polymer. (Azo-Brader<sup>TM</sup> is a trademark of Azon USA Inc.)

Series	Types	AAMA Class at Gateway Size♥	Glazing	Typical Wall Thickness Aluminum Alloy 6063-T6	Frame Depth	Finish Non-standard colors also available - minimum order quantities required.
M-950	Single-Hung	AW40, optional: AW50, AW80		.062	31/4"	Clear Anodized, Bronze Anodized.♣ White (70% Kynar®), Bronze (70% Kynar®). White, Bronze.■
	Fixed	AW40, optional: AW80, AW90				
	Horizontal Slider Single Vent (XO)	CW50, optional: CW55, AW40	1" IGU			
	Horizontal Slider: Center Vent (ZXO) or End Vent (XOX)	CW50				
M-950B	Single-Hung Blast-Resistant	AW50	4" 1011		4 <sup>3</sup> / <sub>4</sub> " with clip, factory applied	
	Horizontal Slider Blast-Resistant	CW50	1" IGU			
	Fixed Blast-Resistant	AW80	1" IGU triple-glazed 2" IGU also available			
M-950/M-950	B single-hung & fixed types also a	vailable as Large Missile Impact per the Flori	da Building Commission.	Contact your Wojan s	ales represen	tative or our office for detail
	Single-Hung	CW30, optional: CW50		.050	211/16"	White, Bronze.■ Clear Anodized, Bronze Anodized.♣ with minimum order quantity: White (70% Kynar®), Bronze (70% Kynar®)
M-85	Horizontal Slider Single Vent (XO)	LC25, optional: CW30	3/4" IGU			
	Horizontal Slider with subsill, Single Vent (XO)	CW35, optional: C50				
	Fixed	CW30, optional: CW50, CW65	1" IGU			
M-85 fixed ty	pe also available as Large Missile	Impact per the Florida Building Commission.	Contact your Wojan sale	s representative or our	r office for de	tails.
M1530	Double Llung Tilt In	CW30		.062/.050	31/4"	White, Bronze.■
M1550	Double-Hung Tilt-In	optional: C50	7/8" IGU			
1630H	Double-Hung Tilt-In	CW30	7/6 IGU			
1650H	with 35/6" bottom sash rail	optional: C50				
4500	Project-In Hopper	AW40, optional: AW70, AW90	1	1	Ι	<u> </u>
	Fixed	AW40, optional: AW100	$\dashv$	.080	23/8"	Clear Anodized, Bronze Anodized.♣ White (70% Kynar®), Bronze (70% Kynar®).⁴ White, Bronze.■
	Fixed Blast-Resistant	AW70	1" IGU		3 <sup>7</sup> / <sub>8</sub> " with clip, factory applied	
	Project-Out Awning	AW40, optional: AW65				
	Project-Out Casement	AW40, optional: AW70			2%"	Clear Anodized,

4500	Fixed Fixed Blast-Resistant	AW40, optional: AW100  AW70	1" IGU	.080	3 <sup>7</sup> /8" with clip, factory applied	Clear Anodized, Bronze Anodized.♣ White (70% Kynar®), Bronze (70% Kynar®).♠ White, Bronze.■
4600	Project-Out Awning	AW40, optional: AW65	1" IGU	.080	23/8"	Clear Anodized, Bronze Anodized.♣ White (70% Kynar®), Bronze (70% Kynar®).◆
	Project-Out Casement	AW40, optional: AW70				
	Project-Out Awning Blast-Resistant	AW65			3 <sup>7</sup> /8" with clip,	
	Project-Out Casement Blast-Resistant	AW70			factory applied	White, Bronze.

2125 2140	Sliding Glass Doors	LC25 optional: LC40	3/4" IGU	.062	3½"	Clear Anodized Sills Doors: White, Bronze.  with minimum order quantity: Clear Anodized, Bronze Anodized.  White (70% Kynar®), Bronze (70% Kynar®).
2500 2600	Sliding Glass Doors	LC25, optional: R20 CW40	1" IGU		4¾"	
2800		CW55				
2700	Transom/Side Lite 2500/2600/2800 only	LC25 (2500 Series) CW30 (2600,2800 Series) optional: AW80				

♥ Many window ratings can be increased by downsizing the window and determining maximum performance through testing. Contact your Wojan sales representative or our office for details.

■ AAMA 2603

♦ AAMA 2605

♣ AAMA 611







Visit www.wojan.com for additional product details, drawings, and ratings updates.