

Window and Door Selection Chart

All products feature pour and debridge polyurethane thermal breaks utilizing **Azo-Brader™** technology, with a 10-year pass-through warranty against failure of the polymer. (Azo-Brader™ is a trademark of Azon USA Inc.)



Series	Types	AAMA Class at Gateway Size♥	Glazing	Typical Wall Thickness Aluminum Alloy 6063-T6	Frame Depth	Finish <i>Non-standard colors also available - minimum order quantities required.</i>
M-950	Single-Hung	AW40, optional: AW50, AW80	1" IGU	.062	3 1/4"	Clear Anodized, Bronze Anodized.♣ White (70% Kynar®), Bronze (70% Kynar®).♦ White, Bronze.■
	Fixed	AW40, optional: AW80, AW90				
	Horizontal Slider Single Vent (XO)	CW50, optional: CW55, AW40				
	Horizontal Slider: Center Vent (ZXO) or End Vent (XOX)	CW50				
M-950B	Single-Hung: Blast	AW50	1" IGU		4 3/4" with clip, factory applied	
	Horizontal Slider: Blast	CW50	1" IGU			
	Fixed: Blast	AW80	1" IGU triple-glazed 2" IGU also available			

M-950/M-950B single-hung & fixed types also available as Large Missile Impact per the Florida Building Commission. Contact your Wojan sales representative or our office for details.

M-85	Single-Hung	CW30, optional: CW50	3/4" IGU	.050	2 11/16"	White, Bronze.■ Clear Anodized, Bronze Anodized.♣ <i>with minimum order quantity:</i> White (70% Kynar®), Bronze (70% Kynar®).♦
	Horizontal Slider Single Vent (XO)	LC25, optional: CW30				
	Horizontal Slider with subsill, Single Vent (XO)	CW35, optional: C50				
	Fixed	CW30, optional: CW50, CW65	1" IGU			

M-85 fixed type also available as Large Missile Impact per the Florida Building Commission. Contact your Wojan sales representative or our office for details.

M1530	Double-Hung Tilt-In	CW30	7/8" IGU	.062/.050	3 1/4"	White, Bronze.■
M1550		optional: C50				
1630H	Double-Hung Tilt-In with 3/8" bottom sash rail	CW30				
1650H		optional: C50				

4500	Project-In Hopper	AW40, optional: AW70, AW90	1" IGU	.080	2 3/8"	Clear Anodized, Bronze Anodized.♣ White (70% Kynar®), Bronze (70% Kynar®).♦ White, Bronze.■
	Fixed	AW40, optional: AW100			3 7/8" with clip, factory applied	
	Fixed: Blast	AW70				
4600	Project-Out Casement	AW40, optional: AW70	1" IGU	.080	2 3/8"	Clear Anodized, Bronze Anodized.♣ White (70% Kynar®), Bronze (70% Kynar®).♦ White, Bronze.■
	Project-Out Awning	AW40, optional: AW65				
	Project-Out Awning with Roto Operator §	AW40				
	Project-Out Awning: Blast	AW65			3 7/8" with clip, factory applied	
	Project-Out Casement: Blast	AW70				

2125	Sliding Glass Doors	LC25	3/4" IGU	.062	3 1/2"	Clear Anodized Sills Doors: White, Bronze.■
2140		optional: LC40				
2500	Sliding Glass Doors	LC25, optional: R20	1" IGU		4 3/4"	<i>with minimum order quantity:</i> Clear Anodized, Bronze Anodized.♣ White (70% Kynar®), Bronze (70% Kynar®).♦
2600		CW40				
2800		CW55				
2700	Transom/Side Lite 2500/2600/2800 only	LC25 (2500 Series) CW30 (2600,2800 Series) optional: AW80				

TD5500	Terrace Door	AW40, optional: AW70, AW100	1"	0.090 to 0.125 typical	3 1/4"	Clear Anodized, Bronze Anodized.♣ White, Bronze.■
--------	--------------	-----------------------------	----	------------------------	--------	--

♥ Many window ratings can be increased by downsizing the window and determining maximum performance through testing.

Contact your Wojan sales representative or our office for details.

§ ADA Compliant option per AAMA 513-12 with an average operating force of less than 5 lbf for lock handles and operator. All testing based on AAMA 513-12 without air, water and structural allowances or reductions; but including sampling, test equipment and methodology qualifications.

■ AAMA 2603 ♦ AAMA 2605 ♣ AAMA 611

www.wojan.com | (800) 632-9827

