

# Window and Door Selection Chart

All products feature pour and debridge polyurethane thermal breaks utilizing **Azo-Brader™** technology, with a 10-year pass-through warranty against failure of the polymer. (Azo-Brader™ is a trademark of Azon USA Inc.)



Series	Types	AAMA Class at Gateway Size▼	Glazing	Typical Wall Thickness Aluminum Alloy 6063-T6	Frame Depth	Finish <i>Non-standard colors also available - minimum order quantities required.</i>
M-950	Single-Hung	AW40, optional: AW50, AW80	1" IGU	.062	3¼"	Clear Anodized, Bronze Anodized.♣ White (70% Kynar®), Bronze (70% Kynar®).♦ White, Bronze.■
	Fixed	AW40, optional: AW80, AW90				
	Horizontal Slider Single Vent (XO)	CW50, optional: CW55, AW40				
	Horizontal Slider: Center Vent (ZXO) or End Vent (XOX)	CW50				
M-950B	Single-Hung <b>Blast-Resistant</b>	AW50	1" IGU	4¾" with clip, factory applied		
	Horizontal Slider <b>Blast-Resistant</b>	CW50				
	Fixed <b>Blast-Resistant</b>	AW80	1" IGU <i>triple-glazed 2" IGU also available</i>			

M-950/M-950B single-hung & fixed types also available as Large Missile Impact per the Florida Building Commission. Contact your Wojan sales representative or our office for details.

M-85	Single-Hung	CW30, optional: CW50	3/4" IGU	.050	2 <sup>11</sup> / <sub>16</sub> "	White, Bronze.■ Clear Anodized, Bronze Anodized.♣  <i>with minimum order quantity:</i> White (70% Kynar®), Bronze (70% Kynar®).♦
	Horizontal Slider Single Vent (XO)	LC25, optional: CW30				
	Horizontal Slider with subsill, Single Vent (XO)	CW35, optional: C50				
	Fixed	CW30, optional: CW50, CW65				

M-85 fixed type also available as Large Missile Impact per the Florida Building Commission. Contact your Wojan sales representative or our office for details.

M1530	Double-Hung Tilt-In	CW30	7/8" IGU	.062/.050	3¼"	White, Bronze.■
M1550		optional: C50				
1630H	Double-Hung Tilt-In with 3 <sup>5</sup> / <sub>8</sub> " bottom sash rail	CW30				
1650H		optional: C50				

4500	Project-In Hopper	AW40, optional: AW70, AW90	1" IGU	.080	2 <sup>3</sup> / <sub>8</sub> "	Clear Anodized, Bronze Anodized.♣ White (70% Kynar®), Bronze (70% Kynar®).♦ White, Bronze.■
	Fixed	AW40, optional: AW100				
	Fixed <b>Blast-Resistant</b>	AW70				
4600	Project-Out Casement	AW40, optional: AW70	1" IGU	.080	2 <sup>3</sup> / <sub>8</sub> "	Clear Anodized, Bronze Anodized.♣ White (70% Kynar®), Bronze (70% Kynar®).♦ White, Bronze.■
	Project-Out Awning	AW40, optional: AW65				
	Project-Out Awning with Roto Operator §	AW40				
	Project-Out Awning <b>Blast-Resistant</b>	AW65				
	Project-Out Casement <b>Blast-Resistant</b>	AW70				

2125	Sliding Glass Doors	LC25	3/4" IGU	.062	3½"	Clear Anodized Sills Doors: White, Bronze.■  <i>with minimum order quantity:</i> Clear Anodized, Bronze Anodized.♣ White (70% Kynar®), Bronze (70% Kynar®).♦
2140		optional: LC40				
2500	Sliding Glass Doors	LC25, optional: R20	1" IGU	.062	4¾"	
2600		CW40				
2800		CW55				
2700	Transom/Side Lite <i>2500/2600/2800 only</i>	LC25 (2500 Series) CW30 (2600,2800 Series) optional: AW80				

▼ Many window ratings can be increased by downsizing the window and determining maximum performance through testing.

Contact your Wojan sales representative or our office for details.

§ ADA Compliant option per AAMA 513-12 with an average operating force of less than 5 lbf for lock handles and operator. All testing based on AAMA 513-12 without air, water and structural allowances or reductions; but including sampling, test equipment and methodology qualifications.

■ AAMA 2603    ♦ AAMA 2605    ♣ AAMA 611

[www.wojan.com](http://www.wojan.com) | (800) 632-9827

